

# SL.250 / SL.250 PMUC

Liquid paint marker  
for stainless steel marking

RIGHT  
FOR  
THE  
JOB.

**Markal**<sup>®</sup>

Markal.com



SL.250 is a xylene-free, low-odor, and fast-drying liquid paint marker that meets the European nuclear requirements. The low sulfur and low chloride content allows for safe marking on stainless steel.

SL.250 PMUC is a unique liquid paint marker certified for nuclear plants in France. Each marker is traceable to a manufactured batch number on the PMUC certificate that is required and controlled by EDF. Its low sulfur and low chloride content is safe for use on stainless steel, alloy, and other super alloy metals where corrosion resistance is a requirement.

- Safe for use on stainless steel and other alloy metals where corrosion resistance is a requirement
- SL.250: Paint formula confirmed using a typical analysis to contain:
  - 200 ppm total halogens
  - 200 ppm sulfur
- SL.250 PMUC: Each marker is delivered with a batch number and an official certificate with the product shipment. Official PMUC certification:
  - 200 ppm total halogens (chlorides, fluoride, bromide, iodine)
  - 200 ppm sulfur
- Fast-drying, permanent paint for immediate handling reduces work downtime
- Medium bullet tip resists wear to provide long marking life
- Marking Range: -20°C to 50°C
- Mark temperature resistance: 100°C

#### Industry uses:

- Nuclear-power generation
- Ship building and repair
- Power generation facilities
- Aviation and aerospace
- Oil and gas
- Welding
- Industrial manufacturing
- Metal fabrication

#### Surfaces uses :

- Stainless steel
- Alloy and super alloy metals
- Alloy metals

#### Details:

##### SL.250



- 31200129
- 31200229
- 31200329
- 31200429
- 31200529
- 31200629

##### SL.250 PMUC



- 31600129
- 31600229
- 31600329
- 31600429
- 31600629

*As manufacturer, we cannot control the conditions under which our products are being used or the many factors that have an effect on the use and application of our products. We disclaim liability for any damages caused by using our products. Please always perform compatibility tests to your application/material demands*

LA-CO Industries Inc.  
1201 Pratt Boulevard  
Elk Grove Village, IL 60007-5746  
USA (1) 800.621.4025  
(1) 847.956.7600  
Customer Service@laco.com  
LP95R00009EN

LA-CO Industries Europe S.A.S.  
ALLEE DES COMBES  
PI DE LA PLAINE DE L'AIN  
01150 BLYES  
France  
Tel : +33 (0) 4 74 46 23 23  
info@eu.laco.com

