

UV-Inspector Policheck NDT

UV LED Pocket Lamp – operable without warm-up time



UV-Inspector Policheck NDT Art. no. 142.200.139 Operation voltage 4.8 V (4 x 1.2 V NiMh accumulator) Suitable for applications in: UV source 1 x UV LED Non-destructive testing Lifetime of LED approx. 10,000 h Quality controls • UV intensity at a distance of 400 mm approx. 11,000 µW/cm² Forensic technique Light spot diameter at 1,000 µW/cm² 80 mm Wave length 365 nm Emission half width approx. 9.0 ±1 nm Total weight approx. 480 g 230 x 75 mm Dimensions Risk class acc. to DGZfP Guide EM 6 Ш

Scope of delivery

- Hand lamp incl. 4 rechargeable NiMh accumulators
- UV protective glasses

Optional

Universal charging device

Heidgraben, May 2020 Subject to technical chances

HELLING GmbH · Spökerdamm 2 · 25436 Heidgraben (bei Hamburg) · Tel.: (04122) 922-0 · Fax (04122) 922-201 · E-Mail: info@helling.de




Applications

Non-destructive materials testing



Fluorescent penetrant testing



Fluorescent magnetic particle testing

Criminalistic Investigation



Identification of forged credit cards, banknotes and other materials

Never look into the UV light beam! **Never** look into the UV light beam with focussed optical equipment such as magnifying glasses, tescopes or microscopes. In this context, correction eyeglasses <u>are not</u> <u>regarded as</u> focussed optical equipment.

Danger of eye injuries exist!

Eye protection by UV protection glasses (part of scope of delivery) is urgently recommended!

HELLING GmbH · Spökerdamm 2 · 25436 Heidgraben (bei Hamburg) · Tel.: (04122) 922-0 · Fax (04122) 922-201 · E-Mail: info@helling.de